

# fusion splicer

# PRO-730

## Description

The PRO-730 is a core alignment fusion splicer designed for use within several areas of fiber optic deployment. Whether your application is Premise, OSP or FTTx, splicing with the PRO-730 will get the job done right.

The PRO-730 is designed to work with all the popular fiber types and in all weather conditions. The dual axis view and reversible color monitor with control panels on both sides assures splicer efficiency in any work environment.

Standard accessories include:

Fusion Splicer, AC Adapter, AC Power Cord, Internal Battery, Charger, Spare Electrodes, Cooling Tray, Manual, Case, Cleaver, Fiber Strippers.



## Specifications:

	PRO-730
Applicable Fibers	SM, MM, DS, NZ-DS, EDF
Cladding Diameter	100 to 150um
Cleave Length	16mm (standard)
Average Splice Loss	0.02dB (SM), 0.01dB (MM), 0.04dB (DS), 0.04 (NZDS)
Environmental Conditions	~25 ~ +50 C (temp), 0~95% (humidity), 0~5000m (altitude)
Tension Test	2.0N (Standard)
Monitor	Color LCD @ 200X
Splice Time	8 Seconds
Heater Time	40 Seconds (Best time)
Max Wind Velocity	15 mph
Camera Axis	X axis & Y axis
Languages	English, Spanish, Russian, Chinese, Korean
Auto check fiber end face	Yes
Auto calibrate	Yes
User Programmable	Yes
Interface	RS232
Data Storage	8000 Splices
Power Supply	Internal Battery (12V - 200 splices) / DC Adapter (12V)
Dimensions	6.5 (W) x 5.5 (H) x 6.5 (D) inches
Weight	7.25 lbs

## Ordering Information:

Description	Part Number
PRO-730 - core alignment fusion splicer	30032508

## Optional Accessories

Description	Part Number	Description	Part Number
Battery	30032511	Manual	30032520
Electrodes	30032514	AC Adapter	30032523
Cleaver	30032517	AC Power Cord	30032526

# Wilcom

Specifications and prices are subject to change without notice.

02/11 813-564-001

ISO - 9001:2008 Registered

P.O. Box 508, Laconia, NH 03247

Tel: (603) 524-2622 or (800) 222-1898, Fax: (603) 524-3735

www.wilcominc.com