

# SR SERIES

The SR Series of Swing Racks provide users with an economical solution for mounting 19" EIA equipment to the wall. Three sizes and a 100 lb. weight capacity provide the optimal amount of vertical space for patch panels and switches. A 180° positive stop and stay-open hinge pins makes accessing and mounting equipment easy. Provisions for optional cinch straps provide necessary cable management. Minimal assembly makes set up quick and easy.



Drawings can be found on page 101



PART NO.	DESCRIPTION
<b>GL24SR</b>	Dimensions 23.75"H x 20.75"W x 18.00"D, Usable depth 16.00", Rack spaces 12 RMU, Wt. cap. 100 lbs., Shipping wt. 34 lbs., includes #12-24 screws
<b>GL36SR</b>	Dimensions: 36.00"H x 20.75"W x 18.00"D, Usable depth 16.00", Rack spaces 19 RMU, Wt. cap. 100 lbs., Shipping wt. 44 lbs., includes #12-24 screws
<b>GL48SR</b>	Dimensions 48.75"H x 20.75"W x 18.00"D, Usable depth 16.00", Rack spaces 26 RMU, Wt. cap. 100 lbs., Shipping wt. 54 lbs., includes #12-24 screws

# SRD SERIES



The SRD Series of Swing Racks is designed to provide a deeper (at 24"D) 19" EIA 310-D compliant solution for the mounting of equipment in an area where physical security is not of issue. With a 180° positive stop and weight capacity of 100 lbs., Great Lakes swing racks are designed in three heights (12 RMU, 19 RMU & 26 RMU) with widths of 20.75". In addition to the standard depth of 18.00", this deeper swing rack provides an additional 6" of mounting depth to accommodate the evolving dimensions of rack mounted equipment. Swing racks are easy to assemble, easy to install and accommodate a variety of accessories.



Drawings can be found on page 101



PART NO.	DESCRIPTION
<b>GL24SRD</b>	Dimensions 24.00"H x 20.75"W x 24.00"D, Usable depth 22.00", Rack spaces 12 RMU, Wt. cap. 100 lbs., Shipping wt. 34 lbs., includes #12-24 screws
<b>GL36SRD</b>	Dimensions: 36.25"H x 20.75"W x 24.00"D, Usable depth 22.00", Rack spaces 19 RMU, Wt. cap. 100 lbs., Shipping wt. 44 lbs., includes #12-24 screws
<b>GL48SRD</b>	Dimensions 48.50"H x 20.75"W x 24.00"D, Usable depth 22.00", Rack spaces 26 RMU, Wt. cap. 100 lbs., Shipping wt. 54 lbs., includes #12-24 screws